

**Telescopic
Fusion Pro 120 cm
Anthracite**

EAN 5414425203550

**Energy label**

▪ Energy Efficiency class (EElhood)	A
▪ Annual Energy Consumption (kWh/year) (AEChood)	39,5
▪ Fluid Dynamic Efficiency class (FDEhood)	A
▪ Lighting Efficiency class (LEhood)	A
▪ Grease Filtering Efficiency class (GFEhood)	C

Functions & features

▪ Motor	Integrated
▪ Sound absorber	Integrated
▪ Recirculation	Optional
▪ InTouch function	Standard
▪ Auto stop	▪
▪ Delayed switch off (minutes)	10
▪ Grease filter	8740050
▪ Number of grease filters	4
▪ Grease filter cleaning indication	▪
▪ Recirculation filter cleaning indication	▪
▪ Control method	Touch control
▪ Number of speeds	3 + power
▪ Automatic Power revert (minutes)	6

Dimensions

▪ Product dimensions (WxDxH) (mm)	1200 x 310 x 340
▪ Dimensions cut-out opening (WxD) (mm)	x
▪ Min dimensions cabinet (WxDxH) (mm)	1200 x 310 x 340
▪ Advised mounting height induction hobs (Hmin-Hmax) (mm)	500 - 750
▪ Advised mounting height gas hobs (Hmin-Hmax) (mm)	650 - 750
▪ Advised mounting height ceramic hobs (Hmin-Hmax) (mm)	500 - 750
▪ Diameter outlet (mm)	150
▪ Position exhaust	Top

Lighting

▪ Functional lighting type	Led strip
▪ Functional light dimmable	▪
▪ Number of functional lights	2
▪ Total energy consumption functional light (W)	18
▪ Color functional light (K)	3000

Airflow and noise level


▪ Free airflow (m³/h)	815
▪ Airflow (m³/h) measured according to EN 61591	
▪ Sound regulation according to EN 60704-2-13	

Airflow and noise level

- Airflow duct out speed 1 (m³/h) / Max pressure duct out speed 1 (Pa) 405 / 173
- Airflow duct out speed 2 (m³/h) / Max pressure duct out speed 2 (Pa) 553 / 351
- Airflow duct out speed 3 (m³/h) / Max pressure duct out speed 3 (Pa) 626 / 386
- Airflow duct out max powerspeed (m³/h) (Qboost) / Max pressure duct out max powerspeed (Pa) 701 / 381
- Sound pressure duct out speed 1 (dB(A)) / Sound power duct out speed 1 (dB(A)) 36 / 48
- Sound pressure duct out speed 2 (dB(A)) / Sound power duct out speed 2 (dB(A)) 44 / 56
- Sound pressure duct out speed 3 (dB(A)) / Sound power duct out speed 3 (dB(A)) 47 / 59
- Sound pressure duct out at max powerspeed (dB(A)) / Sound power duct out at max powerspeed (dB(A)) (LWAboost) 50 / 62

Technical specifications

- Maximum power (W) 124
- Voltage appliance (V) 230
- Frequency (Hz) 50
- Power consumption in stand-by-mode (Ps) (W) 0,25
- Net weight (kg) 18
- Length power supply cable (m) 1,1



Installation accessories

Back panel & chimney extensions

- 88408160 Chimney extension

Additional accessories

- 840029 Remote control

Accessories

Recirculation kit



8740400 Monoblock recirculation set Fusion Pro / Advanced



906450 Exhaust grill for upper cabinet black

